



01 QBT 450™ ROOF TRAY

02 AIR-Z 3D WOVEN MESH

03 QBT 450™ CONTINUOUS ALUMINIUM EXTRUSION

04 10-GAUGE STAINLESS STEEL PAN HEAD
50MM, OR 2.8 X 50 mm FLAT HEAD R-DRIVE
GALV NAILS

05 45 X 70 mm H3.2 TREATED TIMBER BATTEN @ 450 CENTRES

06 VAPOUR PERMABLE ROOF UNDERLAY

07 20 X 50 mm H3.2 TREATED CAVITY BATTEN

08 ROOF STRUCTURE *

09 INSULATION *

10 10-GAUGE by 100mm purlin and batten screw
REFER TO SECTION 10, TABLE 10.1.2 NZS 3604:2011

* PLEASE CHECK WITH STRUCTURAL ENGINEER FOR LOCAL REQUIREMENTS



QBT 450™
THE INNOVATIVE ROOF SYSTEM



www.qbt450.nz

QUICK BATTEN TRAY SYSTEM - QBT 450™

TYPICAL DETAIL FOR ROOF BUILD-UP

COPYRIGHT RESERVED NO REPRODUCTION OR COPY WITHOUT WRITTEN CONSENT FROM CONSTRUCTION CONNECTION AND CONSULTANCY LTD

Date: 20.05.2020

Scale: 1:2 on A3

REV: 01 **A-02**